

EMSCO GA500 (REF#1916N)



No	Description
1	Continental Emsco GA-500 drawworks powered by two (2) Cat 3406B engines 850 HP,
2	Parkersburg 341 Hydramatic brake, (2) Cat 3406B diesel generators with (2) 300 KW
3	Marathon generator
4	Cantilever mast 18'6" leg spread, 127' height, 350,000# static hook load API category 4 certified, new 14' box on box substructure floor height,
5	(2) F1000 triplex mud pumps with 10" stroke powered by (2) 398 Cat engines (2) tank mud system with 630 bbl capacity Including a 60 bbl slug tank Harrisburg desander (2) 10" cones Harrisburg desilter (10) 5" cones Shale shaker
6	(1) Derrick 503 Supper-G Linear motion
7	(1) 500 bbl water tank
8	250 ton traveling block and hook,
9	Lanshi 250 ton swivel,
10	Lanzhou 17.5" rotary table,
11	(1) C.A.D. 4-station accumulator,
12	(1) 11" x 5000 psi annular BOP,
13	(1) 11" x 5000 psi double ram BOP,
14	(1) 11" x 5000 psi drilling spool BOP,
15	Vertical mount degasser with 30 bbl capacity,
16	(1) 4" x 2" choke manifold rated at 5000 psi,
17	4.5" or 5" drill pipe weight and grade to maintain 100,000 pounds of overpull at 10,000'
18	(21) 6.25" drill collars,
19	Wireline unit,
20	Drift indicator,
21	Upper Kelly valve, Lower Kelly, Inside BOP, Air operated Kelly spinner, air operated drill pipe spinner, air operated hoist, 4.25 square Kelly

EMSCO GA500 (REF#1916N) PHOTOS



EMSCO GA500 (REF#1916N) PHOTOS



EMSCO GA500 (REF#1916N) PHOTOS

